

Incorporating the InfraRed touch technology along with supreme IPS panel colour performance, this display offers the optimum performance for a truly multi-user interactive experience. With the ability to handle up to 20 individual touch points, the TH5565MIS-B1AG offers an exceptional capacity within Retail, Education, Training, Corporate and B2B markets. Features include an ambient light sensor delivering optimal picture quality with the added benefit of saving on power. Incorporating 4mm Protection Glass and AG-coating the display can handle harshest environments from the classroom to Public Domain Retail installation. Landscape and Portrait friendly, with OSD portrait mode support, TH5565MIS-B1AG is designed for a continuous operation. A perfect solution for Interactive Digital Signage.





IPS

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

24/7

1. DISPLAY CHARACTERISTICS

DIAGONAL	54.6"; 138.8cm	
ASPECT RATIO	16:9	
PANEL	IPS LED-Backlit, AG88 Coated Glass	
NATIVE RESOLUTION	Full HD 1080p, 1920 x 1080 (2.1 megapixel)	
BRIGHTNESS	450 cd/m² typical	
BRIGHTNESS	400 cd/m ² with touch panel	
CONTRAST	1100 : 1 typical	
RESPONSE TIME	12 ms	
VIEWING ZONE	horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89°	
TOUCHTECHNOLOGY	infrared, multitouch (20 compatible touch points - HID, supported only under Windows® 7/8/10), activated by finger or pen	
TOUCH POINTS	20	
GLASS THICKNESS	4 mm	
GLASS HARDNESS	7H minimum	
LIGHT TRANSMITTANCE	88%	
DISPLAY AREA H X W	680.4 x 1209.6 mm; 26.8" x 47.6"	
PIXEL PITCH H X V	0.63 x 0.63 mm	
HORIZONTAL SYNC	30 - 83 KHz	
VERTICAL SYNC	50 - 76 Hz	
SYNCHRONIZATION	Separate Sync	
DISPLAY COLOURS	16.7	
MAX. NON-STOP OPERATING TIME	24 hours/day	
ANTI-GLARE COATING	yes	

2. INTERFACES & CONNECTORS

HDCP	yes;
AUDIO-SIGNAL-INPUT	mini jack, RCA L/R(2x)
VIDEO IN	VGA, 3x HDMI, Comp. (RCA), AV, USB Media Player
VIDEO OUT	HDMI (daisy chainable), Comp. (RCA), AV
AUDION IN	Audio (L/R, RCA), Mini Jack
AUDIO OUT	Audio (L/R, RCA), speakers
CONTROLS	RS232C (IN/OUT), RJ45 (LAN), USB, IR Extender
USB MEDIA PLAYER	yes

3. SPECIAL FEATURES

CONTROLS	On-Screen-Display in 9 languages (EN, FR, NL, DE, PL, RU, JP, CZ, RU) controlled by back controls or a remote control
USER CONTROLS	picture (picture mode, backlight, contrast, brightness, saturation, hue, sharpness, sharpness booster, colour temp., noise reduction, reset, adv. colour settings, base colour adj., adaptive contrast, ambient light sensor) sound (balance, adv. sound settings, HDMI audio, spectrum analyser, media player, schedule, display wall) setting (language, network settings, control setting, set monitor ID, energy saving settings, aspect, VGA settings, freeze, blue screen, touch feature, anti image retention, OSD rotation, OSD info box, IR out, opening logo, information, all reset)
SPEAKERS	2 x 10 W (Stereo)
SAFETY	CE, CB, TÜV-Bauart, CU
VESA MOUNTING	400 x 400 mm
COLOUR	Black
EXTERNAL CONTROLS	yes
ORIENTATION	landscape / portrait (incl. OSD portrait support)
FANLESS DESIGN	yes
METAL BEZEL	yes

4. ACCESSORIES

INCLUDED ACCESSORIES	power cable, VGA signal cable, HDMI signal cable, USB cable, remote control, batteries (2x), touch pen
	(3x), cable ties, iiyama logo sticker, quick start guide, safety guide

5. POWER MANAGEMENT

POWER SUPPLY	AC 100 - 240 V, 50 / 60 Hz
POWER SUPPLY UNIT	internal
POWER USAGE	106 W typical; max. 0.5 W in Power management mode
POWER MANAGEMENT	VESA DPMS


6. EU ENERGY EFFICIENCY LABEL

ENERGY EFFICIENCY CLASS	В	

7. DIMENSIONS & WEIGHT

DIMENSIONS W X H X D	1265.6 x 736.5 x 72 mm
WEIGHT	37.5 kg

This is information under Regulation (EU) No 1062/2010.
*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION (). ALL RIGHTS RESERVED.